

19, 20, 90

SMITTY'S SUPPLY, INC.
POST OFFICE BOX 530
ROSELAND, LA 70456
504/748-9687

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME:
SMITTY'S SUPPLY, INC.
63399 HWY 51 N
P.O. BOX 530
ROSELAND LA 70456
DARRYL MILLER

PRODUCT NAME: Super S Bar & Chain Oil
HAZARD MATERIAL ID SYSTEM:
H-1 F-1 R-0 PP-B

SECTION 1 - DESCRIPTION

PRODUCT NAME: Super S Bar & Chain Oil
DOT SHIPPING NAME: N/A
DOT HAZARD CLASS: Non Hazardous
CAS REGISTRY NUMBER: 64742-52-5
CHEMICAL NAME: Petroleum hydrocarbon
PREPARER: Chip Armstrong,

SECTION 2 - HAZARDOUS INGREDIENTS

COMPONENTS: Naphthenic distillates with trade secret additives

SECTION 3 - PHYSICAL DATA

BOILING POINT, DEG F: above 500
MELTING POINT, DEG F: N/A
SPECIFIC GRAVITY: 0.88
APPEARANCE: Amber
VAPOR PRESSURE: negligible
VAPOR DENSITY: above 5
SOLUBILITY IN WATER: not soluble
ODOR: mineral oil

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT, DEG F: above 300
EXTINGUISHING MEDIUM: water fog, foam, dry chemical, carbon dioxide
SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool exposed containe
Fire fighting personnel should use respiratory protection.
UNUSUAL FIRE EXPLOSION HAZARDS: product of combustion includes fumes & CO2

SECTION 5 - REACTIVITY HAZARDS

STABILITY: stable
HAZARDOUS POLYMERIZATION: will not
HAZARDOUS DECOMPOSITION PRODUCTS: carbon monoxide upon combustion
MATERIAL TO AVOID: strong oxidizer
CONDITION TO AVOID: open flame

SECTION 6 - HEALTH HAZARD INFORMATION

ROUTE OF ENTRY: INHALATION SKIN INGESTION
ACUTE OVEREXPOSURE: may cause reversible eye and skin irritation; prolonged skin exposure may cause dermatitis; ingestion may cause cramps & diarrhea
breathing mists may cause dizziness
CHRONIC OVEREXPOSURE: defined by IARC as Class I mineral oil
CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN:
NATIONAL TOXICOLOGY PROGRAM IARC MONOGRAPHS OSHA
 YES NO YES NO YES NO

THRESHOLD LIMIT VALUE: 5 mg/cubic meter as mist
EMERGENCY AND FIRST AID: in all cases remove source of exposure
1. INHALATION: unlikely to occur except as mist
2. EYES: flush with water for at least 15 minutes or until irritation subsides
3. SKIN: wash well with soap and water; remove oil soaked clothing; wash clothes before reuse; if irritation develops, consult physician
INGESTION: DO NOT induce vomiting; consult physician; contains solvent

SECTION 7 - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: normally not required with adequate ventilation; if exposure exceeds limits, use NIOSH/MSHA approved air respirator
VENTILATION: if mists are present, provide adequate ventilation to control level below the Permissible Exposure Limit
PROTECTIVE GLOVES: impermeable gloves EYE PROTECTION: goggles
OTHER: none usually required

SECTION 8 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

HANDLING & STORAGE PRECAUTIONS: Keep away from fire, flame & sparks
OTHER PRECAUTIONS: never wear oil soaked clothing; discard oil soaked shoes
affix proper warning labels on containers according to 29 CFR 1010.1200
IN CASE OF SPILLS: no unusual hazard; use pump and/or oil absorbent; keep from entering waterways and sewers
WASTE DISPOSAL METHODS: dispose according to current local, state and federal regulations; consider recycling; NOTE: material may become a hazardous waste through use

NOTE: The above information is based on data of which we are aware and is believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. American Lubricating Company, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, we assume no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.